

# WALL-MOUNTED WIRED TEMPERATURE CONTROL EQUIPMENT

## ROOM THERMOSTATS SERIES ZEFIRO 120 X 80



CODE DESCRIPTION PACKAGE

**1TP TE520A**  
**1TP TE520B**

**Digital thermostat 3V series "ZEFIRO" 120x80, anthracite colour**  
**Digital thermostat 3V series "ZEFIRO" 120x80, white colour**

**10**  
**10**



*backlit display*

Power supply 3V – 2x1.5V AA alkaline  
LCD display, 2" 2/3 backlit  
1 potential-free changeover contact output: 8(2)A/250Va.c.  
ON/OFF operation with adjustable differential switch 0.2 – 2°C or proportional with control period 7/10/13/20 minutes  
Temperature levels 2 + anti-freeze  
Temperature adjustable by 0.1°C sets  
Telephone control input

LOW BAT indicator  
Relay status indicator  
SUM/WIN control  
Password-protected MAX and MIN temperature set lock  
Detection t correction according to product positioning  
Wall-mounting and/or semi-recessed installation  
Dimensions (LxVxH) 120 x 27.6 x 82

**1TP TE521A**  
**1TP TE521B**

**Digital thermostat 230V series "ZEFIRO" 120x80, anthracite colour**  
**Digital thermostat 230V series "ZEFIRO" 120x80, white colour**

**10**  
**10**



*backlit display*

Power supply 230V a.c. 50-60Hz  
LCD display, 2" 2/3 backlit  
1 potential-free changeover contact output: 8(2)A/250Va.c.  
ON/OFF operation with adjustable differential switch 0.2 – 2°C or proportional with control period 7/10/13/20 minutes  
Temperature levels 2 + anti-freeze  
Temperature adjustable by 0.1°C sets  
Telephone control input

Timed or fixed backlighting  
Relay status indicator  
SUM/WIN control  
Password-protected MAX and MIN temperature set lock  
Detection t correction according to product positioning  
Wall-mounting and/or semi-recessed installation  
Dimensions (LxVxH) 120 x 27.6 x 82

**1TP TE525B**

**Digital thermostat 230V series "ZEFIRO" 120x80, with GSM modem - white colour**

**1**



*backlit display*

Power supply 230V 50-60Hz  
Built-in GSM modem for receiving remote controls  
LCD display, 2" 2/3 backlit  
1 potential-free changeover contact output: 8(2)A/250Va.c.  
ON/OFF operation with adjustable differential switch 0.2 – 2°C or proportional with control period 7/10/13/20 minutes  
Temperature levels 2 + anti-freeze




Temperature adjustable by 0.1°C sets  
Timed or fixed backlighting  
Relay status indicator  
SUM/WIN control  
Password-protected MAX and MIN temperature set lock  
Detection t correction according to product positioning  
Dimensions (LxVxH) 120 x 37 x 82



# WALL-MOUNTED WIRED TEMPERATURE CONTROL EQUIPMENT

## ROOM THERMOSTATS SERIES ZEFIRO 80 X 80



CODE	DESCRIPTION	PACKAGE
<b>1TP TE530A</b>	<b>Digital thermostat 3V series "ZEFIRO" 80 x 80, anthracite colour</b>	<b>10</b>
<b>1TP TE530B</b>	<b>Digital thermostat 3V series "ZEFIRO" 80 x 80, white colour</b>	<b>10</b>
	<p>Power supply 3V – 2x1.5V AAA alkaline                      LCD display, 2" 1/3                      1 potential-free changeover contact output: 5(3)A/250Va.c.                      ON/OFF operation with adjustable differential switch 0.2 – 2°C or proportional with control period 7/10/13/20 minutes                      Temperature levels 2 + anti-freeze                      Temperature adjustable by 0.1°C sets</p>	<p>LOW BAT indicator                      Relay status indicator                      SUM/WIN control                      Temperature setting lock                      Detection t correction according to product positioning                      Dimensions (LxWxH) 84 x 23 x 84</p>
<b>1TP TE531A</b>	<b>Digital thermostat 230V series "ZEFIRO" 80 x 80, anthracite colour</b>	<b>10</b>
<b>1TP TE531B</b>	<b>Digital thermostat 230V series "ZEFIRO" 80 x 80, white colour</b>	<b>10</b>
	<p>Power supply 230V a.c. 50-60Hz                      LCD display, 2" 1/3                      1 potential-free changeover contact output: 5(3)A/250Va.c.                      ON/OFF operation with adjustable differential switch 0.2 – 2°C or proportional with control period 7/10/13/20 minutes                      Temperature levels 2 + anti-freeze</p>	<p>Temperature adjustable by 0.1°C sets                      Relay status indicator                      SUM/WIN control                      Temperature setting lock                      Detection t correction according to product positioning                      Dimensions (LxWxH) 84 x 23 x 84</p>
<b>1TP TE532A</b>	<b>Digital thermostat 230V series "ZEFIRO" 80x80, for public areas anthracite colour</b>	<b>10</b>
<b>1TP TE532B</b>	<b>Digital thermostat 230V series "ZEFIRO" 80x80, for public areas white colour</b>	<b>10</b>
	<p>Power supply 230V a.c. 50-60Hz                      LCD display, 2" 1/3                      1 potential-free changeover contact output: 5(3)A/250Va.c.                      ON/OFF operation with adjustable differential switch 0.2 – 2°C or proportional with control period 7/10/13/20 minutes                      Temperature levels 2 + anti-freeze                      Temperature adjustable by 0.1°C sets</p>	<p>Inaccessible controls, reserved to installer:</p> <ul style="list-style-type: none"> <li>- temperature SET adjustment</li> <li>- SUM/WIN</li> <li>- ON/OFF</li> <li>- adjustment settings</li> <li>- detection t correction according to product positioning</li> </ul> <p>Dimensions (LxWxH) 89.7 x 27 x 87.4</p>

