

## DOK 010 AND DOK 420 DISPLAYS

DOK is a digital display module, which can be used as an external display for pressure - (PEL), air flow - (IVL), relative humidity - (KLK 100) and temperature transmitters.

Max. display of 1999 (= 3½ -digits) is available with different ranges.

The input signal of 0-10V (DOK 010) or 4-20mA (DOK 420) can be scaled to different units and ranges according to the order.

### NOTE!

The unit of measurement e.g. °C, Pa, %RH, m/s..., the range and the number of decimals must be advised on the order.



### Technical data:

voltage demand	min. 10 Vdc (DOK 420)
supply	24V ac/dc (DOK 010)
display	LCD, 3½-numbers
dimensions	w x h x d
DOK 420/010-K	115 x 115 x 45 mm
DOK 420/010-P	75 x 77 x 25 mm
housing	
DOK ...-K	IP54
DOK...-P	IP00

### Wiring: DOK 420

1	4...20mA +
3	4...20mA -

### Wiring: DOK 010

1	24V ac/dc
2	0 V
3	0 – 10V

### Ordering guide:

Model	Product number	Description
DOK 010-K	1186010	digital display IP54
DOK 010-P	1186011	digital display IP00
DOK 420-K	1186012	digital display IP54
DOK 420-P	1186013	digital display IP00

Products fulfill the requirements of directive 2004/108/EY and are in accordance with the standards EN61000-6-3 (Emission) and EN61000-6-2 (Immunity).

### Produal Oy

Keltakalliontie 18  
48770 Kotka  
FINLAND  
[www.produal.com](http://www.produal.com)

Puh: +358-5-230 9200  
Fax: +358-5-230 9210  
[info@produal.fi](mailto:info@produal.fi)